

Products Summary

- 1, Double girder gantry crane is applicable to the outdoor warehouse or along the railway general loading and unloading and lifting handling operations.
- 2, The crane by the bridge, cart running mechanism, vehicles, electrical equipment.
- 3, Bridge adopts box welding structure, cart running mechanism driven by respectively.
- 4, Wind alarm, break-proof shaft, prevent the various security measures such as tilting is complete.
- 5, All institutions are in controlling indoor controlling. Crane electric form is divided into two kinds of cables and sliding contact line, you can choose any one of when you order it.
- 6, When choosing the crane must fill in the order specification table, to be marked when using the working environment of low temperature and high temperature, and power supply, etc.

Technical Data

Capacity(t)	Span (m)	Lifting Height (m)	Work Duty	Main Lifting Speed (m/min)	Aux Lifting Speed (m/min)	Crab Travelling Speed (m/min)	Trolley Travelling Speed (m/min)	Power (kw)	Rail
5	18~26	10	A5	9.2	-	37.2	37.7	27.8	43kg/m
	30~35	12							
10	18~22	10		8.5	-	37.2	37.7	35.8	
	26	10						44.8	
	30~35	11							
20/5	18~26	10		7.1	9.2	36.6	40.1	65	
	30~35	12					44	73	

32/5	18~26	10
	30~35	12
50/10	18~26	10
	30~35	12
75/20	18~26	12
	30~35	
100/20	18~35	12
160/50	18~35	15
200/50	18~35	15
320/80	18~35	15
400/30	18	18
500/80	28.5	33
600/80	36	22
800/10	36	14

6.3	9.2	29.8	38	89	
			40	107	
5.9	8.5	31	40.1	141.5	QU80
			44	157.5	
3.9	7.2	38.4	3.7~37		146
3.1	7.2	33.9	3.23~32.3		162
3.5	5.9	22.5	2.8~28		242
3.5	5.9	29	2.8~28		299
3.6	6	16.7	2.8~28		476
0.15~1.5	6	10	18		275
0.15~1.5	0.6~6	1.36~13.6	1.6~16		350
0.13~1.3	0.4~4	1.5~15	2.5~25		405
0.1~1	7	0.5~5	1~10		330