

起重量(t) Lifting capacity		3									5																				
起升高度(m) Lifting height		18									18																				
起升速度(m/min) Lifting speed V		16									16																				
物料假比重 false specific gravity of materials		1									≤1																				
工作制度 Working system		FC=25%									A5 (中级)																				
运行速度 Travelling speed		大车 trolley		30(地面操纵); 75(操纵室操纵) ground controlling; room controlling									30(地面操纵); 75(操纵室操纵) ground controlling; room controlling																		
		小车 crab		20:30									20:30																		
抓斗 grab		型号 model	自重(t) dead weight			容积(m ³) volume			型号 model	自重(t) dead weight			容积(m ³) volume																		
		201	2.3			0.75			301	3.1			1.5																		
电动机 motor	用途 use	型号 model		功率(kw) power		转速(r/min) rotation speed			型号 model		功率(kw) power		转速(r/min) rotation speed																		
	起升 hoisting	ZD, 32-4		4.5		1380			ZD, 41-4		7.5		1400																		
	开闭 open and close	ZD, 32-4		4.5		1380			ZD, 41-4		7.5		1400																		
	大车运行 地面/操纵室 trolley travelling floor/control room	ZDY(D)21-4/ZDR0 0-4(D)		2×0.8 / 2×1.5		1380			ZDY(D)21 -4/ZDR00-4(D)		2×0.8 / 2×1.5		1380																		
	小车运行 crab travelling	ZDY ₁ (D)21-4		2×0.8		1380			ZDY21-4		2×0.8		1380																		
跨度span(m)		7.5	9	10.5	12	13.5	15	16.5	19.5	22.5	7.5	9	10.5	12	13.5	15	16.5	19.5	22.5												
起重机总重(t)地面/操纵室 total weight of crane floor/control room		4.18	4.33	4.48	4.68	4.89	5.55	5.75	6.85	7.13	5.24	5.14	5.58	6.12	6.37	6.89	7.12	7.67	8.75												
最大轮压(t)地面/操纵室 max. wheel load floor/control room		2.15	2.19	2.23	2.28	2.34	2.50	2.55	2.80	2.94	3.28	3.32	3.36	3.50	3.57	3.70	3.76	3.93	4.20												
基本尺寸 basic dimensions		K		2000			2500			3000			2000			25000			3000												
		B		2500			3000			3500			2500			3000			3500												
		H		~3670																											
		H ₁		530			580			660			745			820			580			660			785			820			875