

SWL rated lifting capacity		t	32/10							
Operational method		m/min	Ground controlling ; Cabin controlling							
speed	main.hook lifting		3(0.3/3)							
	Aux.hook lifting		7(7/0.7)							
	crab travelling		20							
	trolley travelling		ground	20 ; 30						
room		30 ; 40								
Motor	main.hook lifting		ZDX62-6/18.5,(ZDS2.2/18.5)							
	Aux.hook lifting		ZD151-4/13(ZDS1-1.5/13)							
	crab travelling		ZDY123-4/2.2x2							
	trolley travelling	ground	ZDY123-4/2.2x2	ZDY131-4/3x2						
room		ZDR112L2-4/3.0x2	ZDR125-4/4.6x2							
Electric Hoist			WH164;CD1(MD1)							
Lifting Height		m	9;12;16;24							
working track recommended			A3--A5							
Power source			3-phase A.C.50Hz;380V							
trolley track recommended			43KG/M							
Span		m	7.5	10.5	13.5	16.5	19.5	22.5	25.5	
Max.wheel presure		KN	167	184	196	206	215	224	233	
Crane weight	ground controlling	kg	12530	14660	16360	18870	21650	24260	27060	
	Cabin controlling	kg	13430	15560	17260	19770	22550	25160	27960	